



MAX INCLINED VIBRATING SCREEN

Demanding applications and specifications require screening equipment to exceed user expectations. McLanahan's MAX Inclined Vibrating Screens provide a solution for all your heavy-duty applications, including minerals, aggregates and more. Capable of separating coarse feed material from finer materials, these vibrating screens are a low headroom design. Each screen is built with maximum strength steel to withstand heavy loading and with the durability to give you longer wear life. MAX Inclined Vibrating Screens are available in a range of sizes from 5'x16' to 8'x24' (1.5mx4.9m to 2.4mx7.3m). They are designed to fit into any existing structure and operation with no rework.

Simpler Maintenance, Safer Operation

McLanahan's MAX Inclined Vibrating Screens were designed with operator safety in mind. The sideplates feature cross beam inspection ports that allow you to inspect inside tubes for failures when the tube is not visible due to abrasion resistant lining. This also eliminates the need for operators to crawl between decks for inspections. Foreign material that can corrode or abrade the inside of the cross members causing premature failure can be flushed out via cross beam inspection ports. The straight shaft features jacking bolts in the mechanism tube to support the shaft during bearing change outs, eliminating the need for a crane to suspend the shaft or the chance of the shaft tipping over and injuring workers, creating a safer work environment and decreasing downtime.

Built To Keep You Running

Many of the features of the MAX Inclined Vibrating Screen improve maintainability for increased uptime. Independent cross members allow you to replace only worn tubes and not the complete deck frame. Replacement cross members are shorter, and have machined and matched shims to allow easy installation in areas with limited clearance. All components slide onto the shaft, allowing for easy removal and installation of replacement parts. The direct drive system eliminates the requirement for a pivoting motor base to keep belt tension on start-up, which can be troublesome to maintain and eventually fail over time. Jacking screws on the motor base make belt tensioning easy. Speed can be adjusted by simply replacing the motor sheaves and can be varied from 700-900 rpms without a change to the driven sheave. MAX Inclined Vibrating Screens come with 150mm bearings as standard across the complete size range of the MAX Screen line.

Durable Design

The MAX Inclined Vibrating Screen is designed to be durable for the longest useful wear life and with maximum strength steel to withstand heavy loading. Sideplates are a fully bolted construction that reduces/eliminates crack propagation due to stress riser in the steel caused by welding and provide the ability to quickly replace worn components without cutting. These sideplates also utilize A572 Gr. 50 plate as standard, giving it 45% higher yield strength than traditional A36 plating. The mechanism is a custom one-piece machined shaft for maximum strength and force output with bolt-on counter weights for easy stroke adjustments. It features a labyrinth seal to deter oil contamination and eliminate the need for a standard breather, which is prone to plugging and failure. The quick change spring kit allows the removal of the spring pack with only minimal vertical clearance and no overhead crane is required. This saves the customer money, as well as reduces downtime and increases worker safety while changing out the springs.

